201410
OGWSD 300 P3K-TSSL
Frame light barrier

- Baffle protection at the optics
- Metal potentiometer
- Cross bar, removable
- Air nozzle for the optics
- NO/NC, switchable
- Variable operating principle: dynamic or static
- Sensitivity adjustment
- Pulse stretching adjustable
- High resolution
- Short activation time





1) sensitivity
2) NO/ NC
3) static/dynamic
4) Sensing surface
5) Transmitter
6) Receiver

BK: black BN: brown BU: blue

Function

Technical data (typ.)	+20°C, 24 V DC
Service voltage	22 … 26 V DC
No-load current (max.)	50 mA
Insulation voltage endurance	500 V
Housing material	Aluminum (Black, Anodized)
Protection class	III, operation on protective low voltage
Operating principle	Dynamic/static switchable
Switching output	pnp, 200 mA, NO/NC, switchable
Voltage drop (max.)	2,5 V
Pulse stretching	0,1 … 150 ms adjustable
Light source	LED
Color	Infrared
Wavelength	940 nm
Modulation	Clocked
Ambient light immunity	8 kLx
Detection range	300 x 397,5 mm
Resolution	Ø 5,0 mm (dynamic), Ø 10,0 mm (static)
Sensitivity adjustment	Potentiometer
Activation time	0,10 ms
Release time	0,10 … 150 ms
Ambient temperature during operation	0 … +60 °C
Protection type	IP 67
Connection	Connector, M8, 3-pin

© di-soric . Right to change reserved . 13.02.2021 . Page 1

201410
OGWSD 300 P3K-TSSL
Frame light barrier

Technical data (typ.)	+20°C, 24 V DC
Connection cable	TK …

More information / accessories	https://www.di-soric.com/201410

© di-soric . Right to change reserved