




210629
OGL 120 G3-T3
Angled light barrier

- 4 operating modes as an IO-Link parameter
- Switch-on/off delay as an IO-Link parameter
- Diagnostics with IO-Link
- Metal casing
- Sensitivity is adjustable
- High switching frequency
- Light/dark switching
- Bright ring LED
- High protection type
- 5-year warranty



Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10 ... 30 V DC (Supply Class 2)
No-load current (max.)	40 mA
Insulation voltage endurance	500 V
Leg length internal	120/120 mm
Housing dimensions	150 x 150 x 12 mm
Housing material	Die-cast zinc (powder-coated)
Material	Mineral glass (Optics)
Protection class	III, operation on protective low voltage
Operating principle	Optical
Evaluation	digital
Design	Angle
Switching output	Push-pull, 200 mA, NO/NC, switchable
Voltage drop (max.)	1,0 V
Interface	IO-Link (V1.1, COM2 38.4 kBd, Smart Sensor Profile)
Light source	LED
Color	Infrared
Wavelength	880 nm
Modulation	Clocked
Ambient light immunity	20 kLx



210629
OGL 120 G3-T3
Angled light barrier

Technical data (typ.)	+20°C, 24 V DC
Range	158 mm (optical axis)
Resolution	Ø 0,5 mm, Ø 0,4 mm, Ø 1,5 mm, Ø 0,5 mm (min. 0.4 mm)
Reproducibility	0,03 mm, 0,03 mm, 0,03 mm, 0,03 mm
Sensitivity adjustment	Potentiometer
Switching frequency	5.000 Hz / 1.500 Hz / 250 Hz / 8.000 Hz
Shock/vibration load	10 ... 55 Hz / 0,5 mm / 30 g
Ambient temperature during operation	-25 ... +60 °C
Protection type	IP 67
Connection	Connector, M8, 3-pin
Connection cable	TK ...
More information / accessories	https://www.di-soric.com/210629