




213004
LAT45-10MP3-B5
Laser distance sensors

- IO-Link
- Long range
- Very good color and surface independence
- Red-light laser for simple alignment
- Measured values on display
- Easy to operate
- Robust metal housing



Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	18 ... 30 V DC (Supply Class 2)
No-load current (max.)	150 mA
Housing dimensions	45 x 52 x 42 mm
Housing material	Die-cast zinc (Black, painted)
Material	Glass (Window)
Weight	309 g
Protection class	III, operation on protective low voltage
Switching output	pnp (1x), 200 mA, NO/NC, configurable
Interface	<ul style="list-style-type: none"> ■ IO-Link V1.1, COM2 ■ Smart Sensor Profile
Light source	Laser
Laser class	2 (IEC 60825-1)
Color	red
Background suppression	10.000 ... 100.000 mm
Light spot size	18 x 20 mm (at distance of 10 m)
Ambient light immunity	100 kLx
Measuring range	200 ... 10.000 mm (90 % remission)
Resolution	1,0 mm (90% remission, measuring frequency 15 Hz)
Reproducibility	4.5 ... 50 mm (90% remission, measuring frequency 15 Hz)
Sensitivity adjustment	Keypad



213004
LAT45-10MP3-B5
Laser distance sensors

Technical data (typ.)	+20°C, 24 V DC
Display	LED Green - Status, yellow - Switching output
Switching frequency	5,0 Hz
Ambient temperature during operation	-10 ... +60 °C
Protection type	IP 67
Connection	Connector, M12, 5-pin
Connection cable	VK ... /5
More information / accessories	https://www.di-soric.com/213004