




201471
OLVTI 41 P3K-IBS
Glass fiber-optic amplifier

- Sensitivity adjustable via external teach input or via buttons
- Metal casing
- Red light
- High switching frequency
- Light/dark switching
- Metal connector
- High protection type



Function										
										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10 ... 35 V DC
No-load current (max.)	45 mA
Insulation voltage endurance	500 V
Housing material	Die-cast zinc (painted)
Protection class	III, operation on protective low voltage
Amplifier for	Glass fiber optics M18
Evaluation	digital
Switching output	pnp, 200 mA, NO/NC, programmable
Voltage drop (max.)	2,8 V
Light source	LED
Color	red
Wavelength	660 nm
Modulation	Clocked
Ambient light immunity	50 kLx
Range	60 mm
Switching hysteresis (max.)	12 %
Reproducibility	< 2 %
Operating elements	3 (Teach, Man-, Man+)
Sensitivity adjustment	Teach button, Remote teach
Display	LED Green - Run, yellow - Output, Red - Teach / Error



201471

OLVTI 41 P3K-IBS

Glass fiber-optic amplifier

Technical data (typ.)

+20°C, 24 V DC

Switching frequency

1.500 Hz

Ambient temperature during operation

-10 ... +60 °C

Temperature drift

0,3 %/K

Protection type

IP 65

Connection

Connector, M12, 4-pin

More information / accessories

<https://www.di-soric.com/201471>