




207460
DCC 12 VHD 2 PS-B3-78-7
Inductive proximity sensor

- High-pressure resistant version up to 500 bar
- High-temperature resistant up to 100 °C permanent temperature
- Housing and sensing face made of stainless steel
- Integrated amplifier
- Short-circuit protection
- Starting pulse suppression



- 1) Width over flats 17 mm 3) O-ring + support ring BK: black BN: brown BU: blue
 2) Width over flats 10 mm

Function



Technical data (typ.)

+20°C, 24 V DC

Service voltage	10 ... 30 V DC
No-load current (max.)	10 mA
Insulation voltage endurance	500 V
Installation type	Flush
Thread	M12 x 1
Housing material	Stainless steel (V2A 1.4301 / AISI 304)
Protection class	III, operation on protective low voltage
Operating principle	inductive
Evaluation	digital
Design	Thread
Characteristics	< 500 bar, high-pressure resistant
Product series	Pressure-resistant
Switching output	pnp, 200 mA, NO
Voltage drop (max.)	2,4 V
Switching distance (SN)	2 mm
Standardized measuring plate	10 x 10 x 1 mm
Switching hysteresis (max.)	15 %
Switching frequency	400 Hz
Ambient temperature during operation	-25 ... +100 °C
Protection type	IP 68 / IP 69K



207460

DCC 12 VHD 2 PS-B3-78-7

Inductive proximity sensor

Technical data (typ.)

+20°C, 24 V DC

Connection

Connector, M12

Connection cable

VK ...

More information / accessories

<https://www.di-soric.com/207460>